

# Dawnprene TPE TKE-70A

TPE

TPE

## Features:

It is a green thermoplastic elastomer (TPE) material. This material combines good physical properties, chemical resistance and elasticity, designed for lawn filling. This grade of TPE can be processed on conventional thermoplastics equipment for extrusion. It is completely recyclable.

<b>(GENERAL)</b>			
(Application)	Lawn fill		
RoHS Compliance	RoHS		
(Color)	Green		
(Form)	Pellet		
(Processing Method)	/		
(Revision Date)	2022-02-16		
<b>Physical</b>	<b>Typical Value</b>	<b>Unit</b>	<b>Test Method</b>
(Density)	1.59	g/cm <sup>3</sup>	ASTM D792
<b>(Hardness)</b>			
Shore Hardness(Shore A, 10 sec,2	68	A	ASTM D2240
- 2			
Tensile strength-parallel flow direction 2	2.7	MPa	ASTM D412
- 2			
2	720	%	ASTM D412
100% - 2	1.2	Mpa	ASTM D412
300% - 2	1.4	Mpa	ASTM D412
- 2	16	KN/m	ASTM D624
1. 120 100 2 , .			
Above testing data is tested by injection sample block, cutting by the sheet size is 120 100 2 .			
2. .			
The properties is typical performance, is not regarding as technical index or agreement.			
SHANDONG DAWN POLYMER CO.,LTD			
: . 265703			
Address: Zhenxing Road, Longgang Economic Zone, Longkou, Shandong, China. 265703			
( ) 0086-535-8868588; ( ) 0086-535-8833988			
Tel: (Foreign Trade) 0086-535-8868588; (Domestic Trade) 0086-535-8833988			